



HRV/ERV Controls

For Standard Residential, Multi-Family,
and Light Commercial HRV/ERV Models

PRODUCT
SPECIFICATIONS
& TECHNICAL
DATA

Wall-mount controls for Standard Residential, Multi-Family, and Light Commercial HRV/ERV models allow you to easily activate a variety of functions at the touch of a button.

Humidity Control (P/N 611224)




- Activates the HRV/ERV to remove excess humidity as desired; the unit returns to its default operation mode when desired humidity is reached
- Indicates the moisture content (%RH) of the ambient air
- 24 VAC
- Surface mount

20/40/60 Minute Timer (P/N 611228)



- Activates the HRV/ERV to operate on high-speed mode for 20, 40, or 60 minutes
- Works with Digital Multifunction Control (P/N 611242)
- 24 VAC
- Fits inside 2" x 4" service box
- Includes retaining screws and white Decora™-style faceplate

Speed Control (P/N 611229)



- 4 HRV/ERV speeds:
 - » Intermittent mode (successive cycles, low-speed 20-minute exchange, 40-minute stop mode)
 - » Low-speed exterior exchange mode
 - » High-speed exterior exchange mode
 - » Unit stop mode
- 24 VAC
- Includes retaining screws and white Decora™-style faceplate

Mode Control (P/N 611230)



- 4 modes of HRV/ERV operation:
 - » Recirculation mode
 - » Low-speed exterior exchange mode
 - » High-speed exterior exchange mode
 - » Unit stop mode
- 24 VAC
- Includes retaining screws and white Decora™-style faceplate

Digital Multifunction Control (P/N 611242)



- Complete control over HRV/ERV:
 - » Dehumidistat mode
 - » ECO Mode (low-speed air exchange for 20 minutes of every hour)
 - » High Occupancy Mode (high-speed air exchange for 1, 2, or 4 hours when more people are in the space)
 - » Air exchanger maintenance indicator
 - » Relative humidity display
- 1" x 1" Liquid-crystal display
- Blue LED backlight (configurable as a nightlight)
- Compatible with 20/40/60 Minute Timer (P/N 611228)
- 24 VAC
- Fits inside 2" x 4" service box
- Includes retaining screws and white Decora™-style faceplate

WARRANTY

The entire unit is guaranteed for two(2) years, from date of shipment, against all manufacturing defects, provided the material has been installed and operated per manufacturer's instructions and under normal conditions. Warranty is limited to the repair or replacement of the material upon its return freight paid to our factory. This warranty is not transferable and is limited to the original end user.

© 2017 American ALDES Ventilation Corporation. Reproduction or distribution, in whole or in part, of this document, in any form or by any means, without the express written consent of American ALDES Ventilation Corporation, is strictly prohibited. The information contained within this document is subject to change without prior written notice.

American ALDES Ventilation Corporation • 4521 19th Street Court East, Suite 104 • Bradenton, FL 34203 – USA
941.351.3441 • 800.255.7749 • 941.351.3442 (fax) • info@americanaldes.com • www.aldes.us