

# Constant Airflow Regulator Selection Guide



Use this table to select the appropriate CAR-II for your project needs.  
Note: Grilles are not included with these models.

MODEL NAME	TYPICAL APPLICATION		USE		STATIC PRESSURE OPERATING RANGE	DUCT TYPE		FIRE DAMPER INCLUDED
	New Construction	Retrofit	Exhaust	Supply		Round	Square/Rectangular	
CAR-II	X	X	X	X	STANDARD PRESSURE 0.20 to 0.80 in. w.g.	X		
CAR-IIA	X	X	X	X		X		
CAR-SE-II	X	X	X					X
CAR-SS-II	X	X		X				X
CAR-FEA-II	X		X					X
CAR-FSA-II	X			X				X
CERB-WS-II	X		X			X		
CERB-WB-II	X		X			X		
CERB-CS-II	X		X			X		
CERB-CFS-II	X		X			X		X
CERB-CFB-II	X		X			X		X
CSRB-WS-II	X			X		X		
CSRB-WB-II	X			X		X		
CSRB-CS-II	X			X		X		
CSRB-CFS-II	X			X		X		X
CSRB-CFB-II	X			X		X		X
CAR-II-LP	X	X	X	X	LOW PRESSURE 0.10 to 0.42 in. w.g.	X		
CAR-LP-SE-II	X	X	X				X	
CAR-LP-SS-II	X	X		X			X	
CAR-II-HP	X	X	X	X	HIGH PRESSURE 0.60 to 2.40 in. w.g.	X		
CAR-HP-SE-II	X	X	X				X	
CAR-HP-SS-II	X	X		X			X	