



LIGHT COMMERCIAL
E1800L-Fi & E1800L-Ri
 Energy Recovery Ventilator
 400-1500 CFM Range

PRODUCT
 SPECIFICATIONS
 & TECHNICAL
 DATA



E1800L-Fi & E1800L-Ri

The E1800L ventilator provides high-efficiency energy recovery. The unit uses a high latent transfer core that can withstand a wide range of environmental conditions. The E1800L produces approximately **1475 CFM** at 0.20 in.w.g (ESP). It is powerful enough for restaurants, offices, and other small businesses.

The E1800L is ideal for cold-weather applications. The E1800L-Fi shuts down the fan for the outdoor air supply during defrost cycles, while the E1800L-Ri uses a fifth port with a motorized damper to defrost the core with recirculated warm air from inside the building.

FEATURES

- Plate-type high latent transfer cores
- Quiet operation
- Multiple filter options
- Efficient and economical operation
- Indoor application

CASING

Material: Painted galvanized steel
 Insulation: 1"(25 mm)
 Drain Connection: Ø 1/2" (Ø 13 mm)
 Duct Connections: 24" x 8" (610 mm x 203 mm)
 Width: 45-5/8" (1158 mm)
 Height: 29-5/8" (753 mm)
 Depth: 48-7/8" (1242 mm)
 Unit Weight: 245 lbs (111 kg); 258 lbs (117 kg) with recirculation
 Shipping Weight: 300 lbs (136 kg)
 313 lbs (142 kg) with recirculation

PLATE EXCHANGER

Standard: High Latent Transfer
 (sensible and latent heat transfer)
 Quantity: 3
 Pitch: 0.13" (3.3 mm)
 Dimensions: 16.34" x 16.34" x 15.67"
 (415 mm x 415 mm x 398 mm)



MOUNTING

Supplied with base rails. Support rod by others.

BLOWERS

Quantity: 4
 Type: Backward-inclined motorized impeller, direct-drive PSC, variable speed, external rotor

FILTERS

Number: 6
 Type: Aluminum (P/N: 612414)
 Optional: MERV 8 (P/N: 612411), Carbon (P/N: 612413), or High Efficiency/MERV13 Equivalent (P/N: 612412)

Additional Air Pressure Drop with Optional Filters				
Filter Type	Airflow CFM (m ³ /h)			
	600 (1020)	1000 (1700)	1400 (2380)	1800 (3060)
MERV 8	0.04	0.08	0.15	0.22
Carbon	0.04	0.08	0.15	0.22
High Efficiency	0.22	0.35	0.48	0.63

ELECTRICAL REQUIREMENTS

120 VAC, 60 Hz, 14.2 A, 1589 W
 20A breaker required

FROST CONTROL

Cycles controlled by a temperature sensor when outdoor temperatures fall below 14°F (-10°C).

- Standard: Exhaust Defrost (E1800L-Fi)
- Optional: Recirculation Defrost (E1800L-Ri)

CONTROLS

24 VAC, 10 VA output for supply and exhaust dampers
 Low-voltage dry contact (24 VAC, 20 VA) for:

- Occupancy Control (start/stop)
- Fan Interlock (NO and NC)
- Speed Selection
- Exhaust/Recirculation (with E1800L-Ri)

Compatible With:

- Digital Multifunction Control (P/N: 611242FC)
- Mode Control (exchange or recirculation) (P/N: 611230)
- Humidity Control (P/N: 611224)
- Speed Control (Low/Intermittent/High) (P/N: 611229)
- 20/40/60 Minute Timer (P/N: 611228)


APPROVALS

Meets Standards:
 • UL 1812 and C22.2 no113


Listed:




Dimensions



FRONT VIEW





BOTTOM VIEW



SIDE VIEW

Performance



© 2016 American ALDES Ventilation Corporation. Reproduction or distribution, in whole or in part, of this document, in any form or by any means, without the express written consent of American ALDES Ventilation Corporation, is strictly prohibited. The information contained within this document is subject to change without prior written notice.